



喬訊電子工業股份有限公司
 CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



Certificate No: TS 622434 FM 587490

http://www.chyaoshiunn.com.tw E-mail: cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	K
Date Issued	2005/04/25	Data Revised	2022/11/15
Subject : JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.			Issued By: Engineering Dept.

**This specification is referred to 3.50mm DIP & SMT series
 wire to board Power connector.**

**本規格書內容係提供 3.50 mm DIP & SMT 系列產品相關參考，
 其用途為電線端相接於電路板端動力電源連接器**

-INDEX-

- 1.0 Product Name/Part Number & Drawing Number.(產品名稱 / 產品型號及圖面型號)
- 2.0 Construction/Dimensions/Material & Surface Finish.(材質以及表面鍍層)
- 3.0 Characteristic.(產品特性)
- 4.0 Specimen.(樣本圖示)
- 5.0 Applicable Standards.(適用規範)
- 6.0 Mechanical Performance.(機械性能)
- 7.0 Electrical Performance.(電氣性能)
- 8.0 Environmental Performance.(環境性能)
- 9.0 Insertion Force (I.F.) & Withdrawal Force (W.F.) for user reference(插入力與拔出力參考規格)
- 10.0 Caution (注意事項)
- 11.0 Remark (備註).

REV. (版次)	Revision Record (改版變更原因)	Date(日期)	ECN No
D	增加中文敘述 以及增加版次變更註記欄	2010/01/16	EC2010-01-025
E	新增JS-2011-02HK有卡棒Housing	2010/08/23	EC2010-08-001
F	增加10.0 產品使用注意事項	2010/11/26	EC2010-11-008
G	鹽水噴霧週期以電鍍方式區隔為 8 小時與48 小時	2011/05/30	EC2011-05-082
H	修改6.1 ;6.2 ;6.3拔出規格值 ; 增列額定電壓 及耐久性測試 ; 修正(EIA-364) 參考規範	2012/01/20	EC2012-01-015
I	導體及固定片材質, 修改區分為 Phosphor Bronze ; Brass	2012/04/03	EC2012-04-001
J	1 增訂10.1.2項Wave Peak Soldering In- Process Temperature Profile 2.修訂8.9項Solder Ability 附註Tin Plated : 95% / Gold Plated : 75% 3.增訂3.5項Storage of Package以及 3.6 項Floor Life 4.增訂8.8項Cold(Low Temperature)耐寒試驗 , EIA-364-59A	2014/08/19	EC2014-08-019
K	1.刪除JS-2012-XX 2.更新bsi標示	2022/11/15	EC2022-11-015



喬訊電子工業股份有限公司
 CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



http://www.chyaoshiunn.com.tw E-mail:cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	K
Date Issued	2005/04/25	Data Revised	2022/11/15
Subject : JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.			Issued By: Engineering Dept.

1.0 Product Name/Part Number & Drawing Number(產品名稱 / 產品型號及圖面型號): Note: (xx) The number of the circuits.

Product Name(產品名稱)		Part Number(產品型號)	Drawing Number(圖面型號)
Housing	(without Lock) 無卡榫	JS-2011-02	
	(with Lock) 有卡榫	JS-2011-02HK	
Crimp Terminal		JS-2011-T	
Wafer	(with Lock) 有卡榫	JS-2013-02XX ; JS-2013-02(NM)	
SMT Type	(2 in 1 with Lock) 二合一, 有卡榫	JS-2013D-04XX : JS-2013D-04(NM)	
Wafer DIP Type	(without Lock) 無卡榫	JS-20121-02XX : JS-20121-02(NM)	
	(with Lock) 有卡榫	JS-20131-02XX ; JS-20131-02(NM)	
	(2 in 1 with Lock) 二合一, 有卡榫	JS-20131D-04XX ; JS-20131D-04(NM)	

2.0 Construction/Dimensions/Material & Surface Finish(材質以及表面鍍層):

Part Name(零件名稱)		Material(材質)	Surface Finish(表面鍍層)
Crimp Terminal (铆壓端子)		Phosphor Bronze	Stamping after tin- plated (先電鍍後衝壓)
Housing (電線端連接器)		Nylon 66	UL 94V-0
Wafer (電路板端連接器)	JS-20121-02	Contact Pin(導體) : Phosphor Bronze Solder Nail /Tab (固定片/柱) : Brass	Matte-Tin Plated or Tin-Plated
	JS-2013-02	Contact Pin(導體) : Brass Solder Nail /Tab (固定片/柱) : Brass	
	JS-20131-02		
	JS-2013D-04		
	JS-20131D-04		
Base (膠座)		Nylon 9T	UL 94V-0

3.0 Characteristic(產品特性):

Item(項目)	Standard(標準規範)
3.1 額定電流 Rated Current	1A AC/DC With AWG #24 is applied (相對適用於美國電線規格 UL1007 AWG #24)
3.2 額定電壓 Rated Voltage	1400 V AC/DC
3.3 Ambient Temperature Range 環境與操作溫度範圍	(操作使用溫度與濕度範圍) Operating Temp.: -25°C~+85°C ; 85% R.H. Max Including 30°C Terminal Temperature Rise at rated Current , (包括定額電流內, 端子所產生 30°C 以下溫昇)
3.4 Applicable Wire 適用電線	3.4.1 (金屬導體型號) Conductor Construction Size: AWG #24~#28
	3.4.2 (電線絕緣材質外徑) Wire Insulation O.D.: 0.90mm~1.80mm
3.5 Storage of Package 包裝未拆封之保存	Temperature and Humidity Condition 溫濕度條件
	Temperature 溫度 : -10°C~+40°C Percentage Humidity 相對濕度 : 70 % Max
	Term 保存期限
3.6 Floor Life 拆封後使用期限	Housing
	Crimp Terminal & Wafer
3.6 Floor Life 拆封後使用期限	Wafer
	Crimp Terminal
	Refer to 10.0 參照第 10.0 項 (IPC/JEDEC J-STD-020D.1 ; Table 5-1) 3 Months



喬訊電子工業股份有限公司
CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



Certificate No: TS 622434 FM 587490

<http://www.chyaoshiunn.com.tw> E-mail: cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	K
Date Issued	2005/04/25	Data Revised	2022/11/15
Subject : JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.			Issued By: Engineering Dept.

4.0 Specimen(樣本圖示) :

Part Name / Part Number / Picture or Photograph 零件名稱 / 零件型號 / 樣本圖示			
Crimp Terminal JS-2011-T			
Housing With Lock JS-2011-02HK		Housing JS-2011-02	
Wafer DIP Type with Lock JS-20131-02		Wafer SMT Type with Lock JS-2013-02	
Wafer DIP Type JS-20121-02			
Wafer (2 in 1) DIP Type with Lock JS-20131D-04		Wafer (2 in 1) SMT Type with Lock JS-2013D-04	



Type Document	Product Specification	Revised /Edition	K
Date Issued	2005/04/25	Data Revised	2022/11/15
Subject : JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.			Issued By: Engineering Dept.

5.0 Applicable Standards(適用規範):

ANSI/EIA 364 ; EIA/ECA 364 Testing method for electrical connectors.

電子連接器，所適用之 ANSI/EIA 364 ; EIA/ECA 364 測試規範

6.0 Mechanical Performance(機械性能):

Item(項目)		Test Condition(測試條件)	Requirement(規格)
6.1	Insertion & Withdrawal Force 嵌入力與拔出力	Insert and withdrawal with connectors at the speed rate of 25.4 ± 3 mm /minute. (Excluding Plastic Detents 不包含膠座卡榫結合合力) 連接器兩端勘合，以每一分鐘 25.4 ± 3mm 的速率，作嵌入與拔出往返測試 (EIA/ECA 364-13D)	Refer to 9.1 Table 1. 參照第 9.1 項 表格 1
6.2	Wire Pullout Force(Axial) 電線脫離端子包覆之拔出力(軸向)	Pull out the cable from contact terminal at the speed rate of 25.4± 3 mm/minute. 對端子所包覆電線，施以每一分鐘 25.4 ± 3 mm 速率之軸向拔出力 (EIA 364-08B)	AWG#24 size wire 2.0kgf/Min.(30.4N 牛頓)
			AWG#26 size wire 1.5kgf/Min.(19.6N 牛頓)
			AWG#28 size wire 1.3kgf/Min.(14.7N 牛頓)
6.3	Crimp Terminal Retention Force (in Housing) 鉚線端子與膠座之間拔出力	Axial pullout force on the terminal in the housing at the speed rate of 25.4 ± 3 mm per minute. 對於已經存在於膠座當中鉚線端子，施以每一分鐘 25.4 ± 3 mm 速率之軸向拔出力	單一接觸點最小容許值 Per Contact : 1.0kgf/Min.
6.4	Pin Retention Force (in Base) 導體與膠座之間保持力	Axial pullout force on the contact in the base at the speed rate of 25.4 ± 3 mm per minute. (EIA/ECA 364-29C) 對於已經存在於膠座當中金屬導體，施以每一分鐘 25.4 ± 3mm 速率之軸向拔出力	單一接觸點最初容許值 Per Contact Initial : 1.0kgf/Min. 經焊錫性測試後： After Soldering Test : 0.5kgf/Min.



Type Document	Product Specification	Revised /Edition	K
Date Issued	2005/04/25	Data Revised	2022/11/15
Subject :JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.			Issued By: Engineering Dept.

7.0 Electrical Performance(電氣性能) :

Item(項目)	Test Condition(測試條件)	Requirement(規格)
7.1 (Low –Signal Level) Contact Resistance (低階信號) 接觸阻抗	A maximum voltage of 20mV and a maximum current of 100mA are applied to the mate connector. 對組合狀態下連接器，於其兩端施以最大測試電壓 20mV 以及最大測試電流 100mA (EIA/ECA 364-23C) (Does not include wire resistance 不包含電線阻抗)	Contact Resistance: 20 milliohms Max. 最大容許值. 20 毫歐姆
7.2 Insulation Resistance 絕緣阻抗	Apply 500V D/C for 1 minute between adjacent contacts to measure the insulation resistance. 對相鄰兩接觸導體，於一分鐘時間內施予 500V D/C 電壓，並量測其間絕緣阻抗值 (EIA 364-21C)	Insulation Resistance: Initial 1000megohms Min 最初容許值. 1000 兆歐姆
7.3 Withstanding Voltage 耐電壓	Apply 3800V A/C (rms) for 1 minute and the leakage current shall not exceed 0.5mA to the adjacent terminal and ground of the mate connectors. (EIA 364-20C) 對組合狀態下連接器，於其相鄰兩導體末端各施以電壓 3800V A/C(實效值) 時間 1 分鐘，且漏電流必須小於 0.5mA(毫安培)	No breakdown or flashover. 無損毀或者產生火花

8.0 Environmental Performance(環境性能) :

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.1 Durability 耐久性	Mate Connectors up 30 Cycles at a Maximun rate of 10 cycles Per minute prior to environmental test (EIA/ECA 364-09C) 以組合狀態下連接器且未經環境測試，依每分鐘內進行 10 次嵌入與拔出之最大速率，連續 30 次嵌入與拔出往返測試	(After the test) Contact resistance : 40 milliohms Max. 經耐久性試驗後接觸阻抗： 最大容許值 40 毫歐姆
8.2 Temperature Rise (Via Current Cycling) 溫度上昇 (經由電流循環操作)	Mate connector . measure the temperature rise of contact when the maximum rated current is passed 以組合狀態下連接器，通過最大容許電流 量測其導體溫度上昇值 (EIA 364-70B Conditions 1 . Method 1)	Mate connectors Temperature Rise: +30°C/Max. 組合狀態下之連接器溫度 上昇最大容許值 + 30°C



喬訊電子工業股份有限公司
 CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



<http://www.chyaoshiunn.com.tw> E-mail: cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	K
Date Issued	2005/04/25	Data Revised	2022/11/15
Subject : JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.			Issued By: Engineering Dept.

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.3 Vibration 耐振動	<p>A mated connector shall be mounted on a printed Circuit board and subjected to a vibration test of the following conditions.</p> <p>During the test, test current continuity shall be checked. After the test, contact resistance shall be measured.</p> <p>以組合狀態下連接器焊接於電路板作為試驗樣品,依照隨附如下規格要求,進行耐振動試驗,試驗過程中確認是否產生不連續電流(斷電)現象,並於試驗過後量測其接觸阻抗。</p> <p>(EIA/ECA 364-28E-Condition 1)</p> <p>Frequency(頻率): 10~55~10 Hz/minute.</p> <p>Amplitude(振幅): 1.5 mm P-P</p> <p>Direction(方向): 1. Axis of up and down.上下軸向(Y軸) 2. Axis of right the left. 左右軸向(X軸) 3. Axis of front and back.前後軸向(Z軸)</p> <p>Period(週期): 2 hours for each direction. (每一個軸向持續 2 小時)</p>	<p>Initial Contact Resistance :</p> <p>20 milliohms Max.</p> <p>接觸阻抗最初容許值:20 毫歐姆</p> <p>(After the test)</p> <p>Contact Resistance:</p> <p>40 milliohms Max.</p> <p>經耐振動試驗後接觸阻抗 :</p> <p>最大容許值 40 毫歐姆</p>
8.4 Humidity 恆溫恆濕	<p>A mated connector shall be placed in a humidity chamber of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance, the insulation resistance and the dielectric withstanding voltage shall be measured.</p> <p>(EIA 364-31B Conditions III . Method A)</p> <p>以組合狀態下連接器放置於恆定溫度與濕度的空間,依照隨附如下規格要求,進行恆溫恆濕試驗,經試驗過後將樣品置於室溫 1~2 小時,再量測其接觸阻抗、絕緣阻抗、以及耐電壓測試。</p> <p>Temperature(溫度): 40±2°C.</p> <p>Relative Humidity(相對濕度): 90%~95% (RH).</p> <p>Period(週期): 96 hours continuously. (持續 96 小時)</p>	<p>(After the test)</p> <p>Contact Resistance:</p> <p>40milliohms Max.</p> <p>經恆溫恆濕試驗後接觸阻抗 :</p> <p>最大容許值. 40 毫歐姆</p> <p>(After the test)</p> <p>Insulation Resistance :</p> <p>500Megohms Min.</p> <p>經恆溫恆濕試驗後絕緣阻抗 :</p> <p>最小容許值. 500 兆歐姆</p> <p>經恆溫恆濕試驗後測耐電壓 :</p> <p>(After the test)</p> <p>Withstanding Voltage:</p> <p>3800V A/C for 1 minute</p>



喬訊電子工業股份有限公司
 CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



Certificate No: TS 622434 FM 587490

<http://www.chyaoshiunn.com.tw> E-mail: cs@chyaoshiunn.com.tw

Type Document		Product Specification	Revised /Edition	K
Date Issued		2005/04/25	Data Revised	2022/11/15
Subject : JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.				Issued By: Engineering Dept.
Item(項目)	Test Condition(測試條件)		Requirement(規格)	
8.5	Thermal Shock 冷熱衝擊	<p>A mated connector shall be subjected to a thermal shock test of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance, the insulation resistance and the dielectric withstanding voltage shall be measured.</p> <p>以組合狀態下連接器作為試驗樣品，依照隨附如下規格要求，進行冷熱衝擊試驗，經試驗過後將樣品置於室溫 1~2 小時，再量測其接觸阻抗、絕緣阻抗、以及耐電壓測試。(EIA/ECA 364-32D)</p> <p>One Cycle Consists Of: -55°C+0/-3°C for 30 minutes. → Room Temp. 5 minutes ; 85°C+3/-0°C for 30 minutes. → Room Temp. 5 minutes Total Cycles: 5 Cycles.</p> <p>以-55°C+0/-3°C溫度持續 30 分鐘，經室溫 5 分鐘，而後再以 85°C+3/-0°C溫度持續 30 分鐘，再經室溫 5 分鐘，構成一次冷熱循環，總計循環次數 5 次。</p>	Same as paragraph 8.4 同 8.4 章節	
8.6	Thermal Aging 高溫老化試驗	<p>A mated connector shall be placed in a heat oven of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance shall be measured. (EIA 364-17B Conditions III)</p> <p>以組合狀態下連接器放置於加熱烤箱當中，依照隨附如下規格要求，進行高溫老化試驗，經試驗過後將樣品置於室溫 1~2 小時，再量測其接觸阻抗。 Temperature(溫度): 85±2°C.</p> <p>Period(週期): 96 hours continuously . (持續 96 小時)</p>	<p>Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值:20 毫歐姆 (After the test) Contact Resistance : 40 milliohms Max. . 經高溫老化試驗後接觸阻抗 : 最大容許值.40 毫歐姆</p>	
8.7	Salt Spray 鹽水噴霧	<p>A mated connector shall be subjected to a Salt Spray test of the following conditions. After the test , the specimen shall be washed with running water and dried naturally before the measurement of contact resistance. 以組合狀態下連接器作為試驗樣品，依照隨附如下規格要求，進行鹽水噴霧試驗，試驗過後將樣品用清水沖洗並經過自然風乾，而後量測其接觸阻抗。</p> <p>Density(鹽水密度): 5 % in weight. Temperature(溫度): 35±2°C.</p> <p>Period(週期): (Stamping after tin plated for 8 hours 先電鍍後沖壓 8 小時); (Stamping before tin plated for 48 hours 先沖壓後電鍍 48 小時) (EIA 364-26B Conditions B)</p>	<p>Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值:20 毫歐姆 (After the test) Contact Resistance: 40 milliohms Max. 經鹽水噴霧試驗後接觸阻抗 : 最大容許值. 40 毫歐姆</p>	



喬訊電子工業股份有限公司
 CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



http://www.chyaoshiunn.com.tw E-mail:cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	K
Date Issued	2005/04/25	Data Revised	2022/11/15
Subject : JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.			Issued By: Engineering Dept.

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.8 Cold 耐寒試驗 (Low Temperature)	A mated connector shall be placed in a cold chamber of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance shall be measured. (EIA 364-59A Procedure 4) 以組合狀態下連接器放置於低溫空間內, 依照隨附如下規格要求, 進行耐寒試驗, 經試驗過後將樣品置於室溫 1~2 小時, 再量測其接觸阻抗。 Temperature(溫度) : -25±3℃. Period(週期): 96 hours continuously . (持續 96 小時)	Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值: 20 毫歐姆 (After the test) Contact Resistance : 40 milliohms Max. . 經耐寒試驗後接觸阻抗 : 最大容許值. 40 毫歐姆
8.9 Solder Ability 焊錫性	Fluxed soldering section of header shall be dipped in solder of the following conditions. 將連接器 pin 針基板嵌入端, 接觸熱溶狀錫料, 依照隨附如下規格要求, 進行焊錫性試驗 Solder Temperature (焊錫溫度) : 245 ± 5℃. Immersion Period (沉浸週期) : 3 ±0.5 Seconds (操作方式): SMT 料件焊錫位置, 距離導體以及固定片末端 0.5mm DIP 料件焊錫位置, 距離導體以及固定片末端 1.5mm Method : SMT 0.5mm /DIP 1.5mm from contact pin and solder tab tip (EIA 364-52B)	Solder entirely (Tin Plated : 95% / Gold Plated : 75%) of immersed area must show no voids or pinholes. 焊料覆蓋面積必須達到 (鍍錫 95% / 鍍金 75%), 而且不能產生氣孔或空隙
8.10 Resistance To Soldering Heat 焊錫耐熱性	By Reflow Soldering(迴焊適用溫度範圍) : Refer to Temperature Profile 請參考 8.10.1.1 溫度曲線圖 (IPC/JEDEC J-STD-020D.1) By Wave Soldering(波峰焊適用溫度範圍) : Refer to Temperature Profile 請參考 8.10.1.2 溫度曲線圖 (EIA-364-71B) by soldering iron 手工烙鐵焊錫適用溫度範圍 : 350 ± 5℃ 3±0.5 Seconds. (操作方式): SMT 料件焊錫位置, 距離導體以及固定片末端 0.5mm DIP 料件焊錫位置, 距離導體以及固定片末端 1.5mm Method : SMT 0.5mm / DIP 1.5mm from contact pin and solder tab tip (EIA/ECA 364-56C Procedure 3. Conditions A)	No deformation or damage. 不可有變形或損壞


Notes : Flowing Mixed Gas (EIA 364-65A) shall be conduct by Customer request 混合流動氣體測試遵照客戶需求




Type Document	Product Specification	Revised /Edition	K
Date Issued	2005/04/25	Data Revised	2022/11/15
Subject : JS-2011-02/HK JS-2011-T JS-2013-02 JS-20131-02 JS-20121-02 JS-2013D-04 JS20131D-04 Pitch : 3.50mm Wire to Board Power Connector Series.			Issued By: Engineering Dept.

8.10.1 Temperature Profile(溫度曲線圖) :

8.10.1.1 IR-Reflow Peak Soldering In-Lead Free Process 迴焊無鉛制程:



8.10.1.2 Wave Peak Soldering In-Lead Free Process 波峰焊無鉛制程



9.0 Tables & Attachments

9.1 Table 1. Insertion Force (I.F.) & Withdrawal Force (W.F.) for user reference:

No. Of Circuits 極數	AT INITIAL 首次嵌入與拔出(初始值)		AT 30 TH 30 次嵌入與拔出之後	No. Of Circuits 極數	AT INITIAL 首次嵌入與拔出(初始值)		AT 30 TH 30 次嵌入與拔出之後
	I.F. (MAX) 嵌入力	W.F. (MIN) 拔出力	W.F. (MIN) 拔出力		I.F. (MAX) 嵌入力	W.F. (MIN) 拔出力	W.F. (MIN) 拔出力
	02	2.50	0.5		0.40	2 in 1	2.50

Unit : kg/f

10.0 Caution (注意事項) : Parts are made of hydrophilic Polyamide 9T and apt to absorb moisture. Once the vacuum-packing unpacked, please keep parts in the environment of **temperature < 30°C / humidity < 60% RH**, and send to re-flowing **within 72 hours** to prevent parts blistered or deformed during soldering.

PA9T 塑料因具親水之特性，故採用真空包裝以減少吸濕受潮。真空包裝經拆封應避免曝露於溫度高於 30°C，濕度高於 60% RH 的環境中，並在拆封 72 小時內全數使用完畢，以防止後續迴焊製程產生起泡變形現象。

11.0 Remark(備註) : Any change or revision for the product specification will not be announced in advance.

Please contact our sales representative for the latest information.

有關規格書內容經變更或改版，如未能夠及時發佈與通知，煩請連絡我司業務人員以提供產品最新資訊

Reviewed: Tom Shih Approved: Erin Chou Verified: Eddie Chiang