



喬訊電子工業股份有限公司
 CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.



TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677

http://www.chyaoshiunn.com.tw E-mail:cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	G
Date Issued	2010/03/02	Data Revised	2015/02/25
Subject : JS-2330BS-2X JS-2430BS-2X JS-2330 JS-2330B-xxE JS-2430 JS-2430B-xxE Pitch : 5.03mm(Ø2.36mm) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

This specification is referred to Pitch : 5.03 mm(Ø2.36mm) series wire to wire Power connector.
 本規格書內容係提供 Pitch : 5.03mm (公端子外徑 2.36mm)系列產品相關參考，
 其用途為電線端相接於電線端動力電源連接器

-INDEX-

- 1.0 Product Name/Part Number & Drawing Number.(產品名稱 / 產品型號及圖面型號)
- 2.0 Construction/Dimensions/Material & Surface Finish.(材質以及表面鍍層)
- 3.0 Characteristic.(產品特性)
- 4.0 Specimen.(樣本圖示)
- 5.0 Applicable Standards.(適用規範)
- 6.0 Mechanical Performance.(機械性能)
- 7.0 Electrical Performance.(電氣性能)
- 8.0 Environmental Performance. (環境性能)
- 9.0 Insertion Force & Withdrawal Force Requirement.(插入力與拔出力規格值)
- 10.0 Remark (備註).

REV. (版本)	Revision Record (改版變更原因)	Date(日期)	ECN No.
B	鹽水噴霧週期以電鍍方式區隔為 8 小時與48 小時	2011/05/26	EC2011-05-066
C	1.增加耐久性 及溫升 2.刪除硫化氫 3.修正(EIA-364) 參考規範 4.增列額定電壓 5. 增列 JS-2330BS-2; JS-2430BS-2 6.參考原廠規格修改耐電壓2000 A/C (rms)	2012/03/02	EC2012-03-003
D	更正JS-2430BS1-2 'JS-2430BS-2 'JS-2330BS1-2 'JS-2330BS-2 適用 AWG#	2013/06/10	EC2013-06-010
E	1.增訂3.5項Storage of Package以及3.6 項Floor Life 2.變更4.0項JS-2330BS1-2圖示	2014/01/24	EC2014-01-024
F	增訂8.7項Cold(Low Temperature)耐寒試驗 , EIA-364-59A.	2015/02/03	EC2015-02-003
G	1.修訂 6.1 項 Insertion Force : 4.0 kg/f Max , Withdrawal Force : 1.25 kg/f Min / 2 增訂 8.4 項 Cold(Low Temperature)耐寒試驗 , EIA-364-59A / 3. 1.0 項 JS-2330BS-2X 修訂 With AWG #16~20 is applied	2015/02/25	EC2015-02-025



喬訊電子工業股份有限公司
CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



http://www.chyaoshiunn.com.tw E-mail:cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	G
Date Issued	2010/03/02	Data Revised	2015/02/25
Subject : JS-2330BS-2X JS-2430BS-2X JS-2330 JS-2330B-xxE JS-2430 JS-2430B-xxE Pitch : 5.03mm(Ø2.36mm) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

1.0 Product Name/Part Number & Drawing Number(產品名稱 / 產品型號及圖面型號):

Product Name(產品名稱)		Part Number(產品型號)	Drawing Number(圖面型號)
Female Crimp Terminal	(With AWG #14~18 is applied)	JS-2430BS-2H	
	(With AWG #16~20 is applied)	JS-2430BS-2X	
	(With AWG #18~22 is applied)	JS-2430BS-2L	
Male Crimp Terminal	(With AWG #14~18 is applied)	JS-2330BS-2H	
	(With AWG #16~20 is applied)	JS-2330BS-2X	
	(With AWG #18~22 is applied)	JS-2330BS-2L	
Plug with Ear (插頭 有耳)		JS-2430B-XXE	
Plug without Ear (插頭 無耳)		JS-2430-XX	
Receptacle with Ear (插座 有耳)		JS-2330B-XXE	
Receptacle without Ear (插座 無耳)		JS-2330-XX	

Note: (xx) The number of the circuits.

2.0 Construction/Dimensions/Material & Surface Finish(材質以及表面鍍層):

Part Name(零件名稱)	Material(材質)	Surface Finish(表面鍍層)
Crimp Terminal (铆壓端子)	Brass	Stamping after tin plated (先電鍍後衝壓)
Receptacle (插座)	Nylon 66	UL 94V-2
Plug (插頭)		

3.0 Characteristic(產品特性):



Item(項目)	Standard(標準規範)	
3.1 額定電流 Rated Current	12 A AC/DC	
3.2 額定電壓 Rated Voltage	250 V AC(rms)	
3.3 Ambient Temperature Range 環境與操作溫度範圍	(操作使用溫度與濕度範圍) Operating Temp. : -40°C~+105°C ; 85% R.H. Max Including 30°C Terminal Temperature Rise at rated Current , (包括定額電流內, 端子所產生 30°C 以下溫昇)	
3.4 Applicable Wire 適用電線	(金屬導體之型號) Conductor Construction Size: AWG #14~#24	
3.5 Storage of Package 包裝未拆封之保存	Temperature and Humidity Condition 溫濕度條件	Temperature 溫度 : -10°C~+40°C Percentage Humidity 相對濕度 : 70 % Max
	Term 保存期限	Housing Crimp Terminal 2 Years 1 Year
3.6 Floor Life 拆封後使用期限	Crimp Terminal	3 Months

Note: 嵌合面板適用厚度 Applicable Panel Thickness: 1.52 mm Max.



Type Document	Product Specification	Revised /Edition	G
Date Issued	2010/03/02	Data Revised	2015/02/25
Subject : JS-2330BS-2X JS-2430BS-2X JS-2330 JS-2330B-xxE JS-2430 JS-2430B-xxE Pitch : 5.03mm(Ø2.36mm) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

4.0 Specimen(樣本圖示) :

Part Name / Part Number / Picture or Photograph 零件名稱 / 零件型號 / 樣本圖示			
Female Crimp Terminal JS-2330BS-2X / 2L/ 2H		Male Crimp Terminal JS-2430BS-2X / 2L/ 2H	
Receptacle With Ear JS-2330B-XXE		Receptacle Without Ear JS-2330	
Plug With Ear JS-2430B-XXE		Plug Without Ear JS-2430	

5.0 Applicable Standards(適用規範):

ANSI/EIA 364 ; EIA/ECA 364 Testing method for electrical connectors.

電子連接器，所適用之 ANSI/EIA 364 ; EIA/ECA 364 測試規範

6.0 Mechanical Performance(機械性能):

Item(項目)	Test Condition(測試條件)	Requirement(規格)
6.1 Insertion & Withdrawal Force 插入力與拔出力	Insert and withdrawal with connectors at the speed rate of 25.4 ± 3 mm /minute. 連接器兩端勘合，以每一分鐘25.4 ± 3mm 的速率，作插入與拔出往返測試 (EIA/ECA 364-13D) (Excluding Thumb Latch 不包含活動卡榫結合力)	單一接觸點 Per Contact 插入力最大容許值 Insertion Force : 4.0 kg/f Max 拔出力最小容許值 Withdrawal Force : 1.25 kg/f Min



Type Document	Product Specification	Revised /Edition	G
Date Issued	2010/03/02	Data Revised	2015/02/25
Subject : JS-2330BS-2X JS-2430BS-2X JS-2330 JS-2330B-xxE JS-2430 JS-2430B-xxE Pitch : 5.03mm(Ø2.36mm) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

Item(項目)	Test Condition(測試條件)	Requirement(規格)
6.2 Wire Pullout Force(Axial) 電線脫離端子包覆之拔出力(軸向)	Pull out the cable from contact terminal at the speed rate of 25.4± 3 mm/minute. 對端子所包覆電線，施以每一分鐘 25.4 ± 3 mm 速率之軸向拔出力 (CSA C22.2 No.182.3)	AWG#14 size wire 11.34kgf/Min.(111N 牛頓)
		AWG#16 size wire 9.08kgf/Min.(89N 牛頓)
		AWG#18 size wire 9.08kgf/Min.(89N 牛頓)
		AWG#20 size wire 4.54kgf/Min.(44.5N 牛頓)
		AWG#22 size wire 3.63kgf/Min.(35.6N 牛頓)
6.3 Crimp Terminal Retention Force (in Housing) 鍍線端子與膠座間拔出力	Axial pullout force on the terminal in the housing at the speed rate of 25.4 ± 3 mm per minute. 對於已經存在於膠座當中鍍線端子，施以每一分鐘 25.4± 3 mm 速率之軸向拔出力	單一接觸點 Per Contact 最小容許值 9.0kgf/Min.

7.0 Electrical Performance(電氣性能) :

Item(項目)	Test Condition(測試條件)	Requirement(規格)
7.1 (Low –Signal Level) Contact Resistance (低階信號) 接觸阻抗	A maximum voltage of 20mV and a maximum current of 100mA are applied to the mate connector. 對組合狀態下連接器，於其兩端施以最大測試電壓 20mV 以及最大測試電流 100mA (EIA/ECA 364-23C) (Does not include wire resistance 不包含電線阻抗)	Contact Resistance: 20 milliohms Max. 最大容許值 20 毫歐姆
7.2 Insulation Resistance 絕緣阻抗	Apply 500V D/C for 1 minute between adjacent contacts to measure the insulation resistance. 對相鄰兩接觸導體，於一分鐘時間內施予 500V D/C 電壓，並量測其間絕緣阻抗值 (EIA 364-21C)	Insulation Resistance: Initial 1000megohms Min 最初容許值 1000 兆歐姆
7.3 Withstanding Voltage 耐電壓	Apply 2000 A/C (rms) for 1 minute and the leakage current shall not exceed 0.5mA to the adjacent terminal and ground of the mate connectors. 對組合狀態下連接器，於其相鄰兩導體末端各施以電壓 2000 A/C (實效值) 時間 1 分鐘，且漏電流必須小於 0.5mA(毫安培) (EIA 364-20C)	No breakdown or flashover. 無損毀或者產生火花

8.0 Environmental Performance(環境性能) :

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.1 Durability 耐久性	Mate Connectors up 25 Cycles at a Maximun rate of 10 cycles Per minute prior to environmental test 以組合狀態下連接器且未經環境測試，依每分鐘內進行10次嵌入與拔出之最大速率，連續25次嵌入與拔出往返測試 (EIA/ECA 364-09C)	(After the test) Contact resistance : 40 mΩ Max 經耐久性試驗後接觸阻抗 最大容許值 40 毫歐姆



Type Document	Product Specification	Revised /Edition	G
Date Issued	2010/03/02	Data Revised	2015/02/25
Subject : JS-2330BS-2X JS-2430BS-2X JS-2330 JS-2330B-xxE JS-2430 JS-2430B-xxE Pitch : 5.03mm(Ø2.36mm) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

Item(項目)		Test Condition(測試條件)	Requirement(規格)
8.2	Temperature Rise (Via Current Cycling) 溫度上昇 (經由電流循環操作)	Mate connector . measure the temperature rise of contact when the maximum rated current is passed 以組合狀態下連接器，通過最大容許電流 量測其導體溫度上昇值 (EIA 364-70B Conditions 1 . Method 1)	Mate connectors Temperature Rise: +30°C/Max. 組合狀態下之連接器溫度 上昇最大容許值+30°C
8.3	Vibration 耐振動	A mated connector shall be mounted on a printed Circuit board and subjected to a vibration test of the following conditions. During the test, test current continuity shall be checked. After the test, contact resistance shall be measured. 以組合狀態下連接器焊接於電路板作為試驗樣品,依照隨附如下規格要求,進行耐振動試驗，試驗過程中確認是否產生不連續電流(斷電)現象，並於試驗過後量測其接觸阻抗。 (EIA/ECA 364-28E-Condition I) Frequency(頻率) : 10~55~10 Hz/minute. Amplitude (振幅) : 1.5 mm P-P Direction (方向) :1. Axis of up and down.上下軸向(Y 軸) 2. Axis of right the left. 左右軸向(X 軸) 3. Axis of front and back.前後軸向(Z 軸) Period(週期) : 2 hours for each direction. (每一個軸向持續 2 小時)	Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值 20 毫歐姆 (After the test) Contact Resistance: 40 milliohms Max. 經耐振動試驗後接觸阻抗 最大容許值 40 毫歐姆 No discontinuity current is longer than 1 microsecond. 電流中斷現象， 時間不可多於1微秒
8.4	Cold 耐寒試驗 (Low Temperature)	A mated connector shall be placed in a cold chamber of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance shall be measured. 以組合狀態下連接器放置於低溫空間內, 依照隨附如下規格要求, 進行耐寒試驗，經試驗過後將樣品置於室溫 1~2 小時,再量測其接觸阻抗。 (EIA 364-59A Procedure 3) Temperature(溫度) : -40±3°C. Period(週期): 96 hours continuously . (持續 96 小時)	Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值 20 毫歐姆 (After the test) Contact Resistance : 40 milliohms Max. . 經耐寒試驗後接觸阻抗 最大容許值. 40 毫歐姆



Type Document	Product Specification	Revised /Edition	G
Date Issued	2010/03/02	Data Revised	2015/02/25
Subject : JS-2330BS-2X JS-2430BS-2X JS-2330 JS-2330B-xxE JS-2430 JS-2430B-xxE Pitch : 5.03mm(Ø2.36mm) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

Item(項目)		Test Condition(測試條件)	Requirement(規格)
8.5	Humidity (Steady State) 恆溫恆濕	A mated connector shall be placed in a humidity chamber of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance, the insulation resistance and the dielectric withstanding voltage shall be measured. 以組合狀態下連接器放置於恆定溫度與濕度的空間，依照隨附如下規格要求，進行恆溫恆濕試驗，經試驗過後將樣品置於室溫 1~2 小時，再量測其接觸阻抗、絕緣阻抗、以及耐電壓測試。 (EIA 364-31B Conditions II. Method A) Temperature(溫度) : 40±2°C. Relative Humidity(相對濕度) : 90%~95% (RH). Period(週期) : 96 hours continuously. (持續 96 小時)	(After the test) Contact Resistance: 40 milliohms Max. 經恆溫恆濕試驗後接觸阻抗 最大容許值. 40 毫歐姆
			(After the test) Insulation Resistance : 500 Megohms Min. 經恆溫恆濕試驗後絕緣阻抗 最小容許值. 500 兆歐姆
			經恆溫恆濕試驗後耐電壓 (After the test) Withstanding Voltage: 2000V A/C for 1 minute
8.6	Thermal Shock 冷熱衝擊	A mated connector shall be subjected to a thermal shock test of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance, the insulation resistance and the dielectric withstanding voltage shall be measured. 以組合狀態下連接器作為試驗樣品，依照隨附如下規格要求，進行冷熱衝擊試驗，經試驗過後將樣品置於室溫 1~2 小時，再量測其接觸阻抗、絕緣阻抗、以及耐電壓測試。 (EIA/ECA 364-32D Conditions I. Method A) One Cycle Consists Of: -55°C+0/-3°C for 30 minutes. → Room Temp. 5 minutes 85°C+3/-0°C for 30 minutes. → Room Temp. 5 minutes Total Cycles: 5 Cycles. 以-55°C+0/-3°C溫度持續 30 分鐘，經室溫 5 分鐘，而後再以 85°C+3/-0°C溫度持續 30 分鐘，再經室溫 5 分鐘，構成一次冷熱循環，總計循環次數 5 次。	Same as paragraph 8.5 同 8.5 章節



喬訊電子工業股份有限公司
CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



http://www.chyaoshiunn.com.tw E-mail:cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	G
Date Issued	2010/03/02	Data Revised	2015/02/25
Subject : JS-2330BS-2X JS-2430BS-2X JS-2330 JS-2330B-xxE JS-2430 JS-2430B-xxE Pitch : 5.03mm(Ø2.36mm) Wire to Wire Power Connector Series.			Issued By: Engineering Dept.

Item(項目)		Test Condition(測試條件)	Requirement(規格)
8.7	Heat Aging 高溫老化試驗	<p>A mated connector shall be placed in a heat oven of the following conditions. After the test, leave the specimen at room temperature for 1~2 hours before the contact resistance shall be measured. 以組合狀態下連接器放置於加熟烤箱當中, 依照隨附如下規格要求, 進行高溫老化試驗, 經試驗過後將樣品置於室溫 1~2 小時,再量測其接觸阻抗。</p> <p>(EIA 364-17B Conditions 4. Method A)</p> <p>Temperature(溫度): 105±2℃.</p> <p>Period(週期): 96 hours continuously . (持續 96 小時)</p>	<p>Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值 20 毫歐姆 (After the test)</p> <p>Contact Resistance : 40 milliohms Max. . 經高溫老化試驗後接觸阻抗 最大容許值. 40 毫歐姆</p>
8.8	Salt Spray 鹽水噴霧	<p>A mated connector shall be subjected to a Salt Spray test of the following conditions. After the test , the specimen shall be washed with running water and dried naturally before the measurement of contact resistance. 以組合狀態下連接器作為試驗樣品, 依照隨附如下規格要求, 進行鹽水噴霧試驗 , 試驗過後將樣品用清水沖洗並經過自然風乾 , 而後量測其接觸阻抗。</p> <p>(EIA 364-26B Conditions B)</p> <p>Density(鹽水密度): 5 % in weight.</p> <p>Temperature(溫度): 35±2℃.</p> <p>Period(週期): Terminal or contact (Stamping after tin plated for 8 hours) ; Terminal or contact (Stamping before tin plated for 48 hours) 端子或導體(先電鍍後沖壓 8 小時) ; 端子或導體 (先沖壓後電鍍 48 小時)</p>	<p>Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值 20 毫歐姆 (After the test)</p> <p>Contact Resistance: 40 milliohms Max. 經鹽水噴霧試驗後接觸阻抗 最大容許值. 40 毫歐姆</p>

Notes : Flowing Mixed Gas (EIA 364-65A) shall be conduct by Customer request 混合流動氣體測試遵照客戶需求

9.0Remark(備註) : Any change or revision for the product specification will not be announced in advance.

Please contact our sales representative for the latest information.

有關規格書內容經變更或改版, 如未能夠及時發佈與通知, 煩請連絡我司業務人員以提供產品最新資訊

Reviewed: J.M.Chang Approved: Peter Chang Verified: Indiana Huang