



Halogen Free

■ SPECIFICATIONS

- Current Voltage : 125V AC/DC
- Current Rating : 1 A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 100MΩ min
- Temperature Range : - 40°C to + 85°C
- Contact Resistance : 20mΩ max

■ WAFER (SMT Type)

JS-1007V-XX(XX)(XX)-NH
① ② ③ ④

- ① Poles: 06~30
- ② Plated :
Blank: Tin Plated
M: Matte-Tin Plated
G0: Gold Plated
- ③ Blank: Without Mylar
ML: With Mylar
- ④ Material :
NH: Halogen Free
* Material :
1. Base : PA4T-GF30 FR(40) (Halogen Free)
2. Actuator: HTN (FR52G30) (Halogen Free)
3. Contact : Phos. Bronze
. Packing: 800PCS/Reel

Poles	A	B	C	D
06	5.00	10.90	12.60	7.20
07	6.00	11.90	13.60	8.20
08	7.00	12.90	14.60	9.20
09	8.00	13.90	15.60	10.20
10	9.00	14.90	16.60	11.20
11	10.00	15.90	17.60	12.20
12	11.00	16.90	18.60	13.20
13	12.00	17.90	19.60	14.20
14	13.00	18.90	20.60	15.20
15	14.00	19.90	21.60	16.20
16	15.00	20.90	22.60	17.20
17	16.00	21.90	23.60	18.20
18	17.00	22.90	24.60	19.20
19	18.00	23.90	25.60	20.20
20	19.00	24.90	26.60	21.20
21	20.00	25.90	27.60	22.20
22	21.00	26.90	28.60	23.20
23	22.00	27.90	29.60	24.20
24	23.00	28.90	30.60	25.20
25	24.00	29.90	31.60	26.20
26	25.00	30.90	32.60	27.20
27	26.00	31.90	33.60	28.20
28	27.00	32.90	34.60	29.20
29	28.00	33.90	35.60	30.20
30	29.00	34.90	36.60	31.20

喬訊電子工業股份有限公司
CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞	1:1	mm	.0 ±0.30	△				△			
CHECKED BY	PROJ	VER NO.	.00 ±0.20	△				△			
周家慶	⊕ □	a	.000 ±0.10	△				△			
DRAWN BY	DATE	SIZE	ANGLE	△							
黃廣珍	2014.05.07	A4	0° ±1°	△							
			.0° ±	△							
			SHEET 1/1	△							

PART NO JS-1007V-XX(XX)(XX)-NH
1.00mm NON-ZIF FPC SMT Horizontal Dual Contact Style

CUSTOMER
Conforms to The RoHS Instruction