



■ SPECIFICATIONS

- Voltage Rating : 100V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC /minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 40°C to + 105°C
- Contact Resistance : 10mΩ max

■ SIP SOCKET

- Part No. : JS-11791SFTD-XX
- Code No: ①
- ① Poles : 2-40(Single Row)
- Material : Beau : Beryllium Copper , Gold Plated  
Sleeve Barrel : Brass , Tin Plated  
Base : PPS UL94V-0
- Q' ty : 1,000 pcs./Bag

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2	2.54	5.08	22	53.34	55.88
3	5.08	7.62	23	55.88	58.42
4	7.62	10.16	24	58.42	60.96
5	10.16	12.70	25	60.96	63.50
6	12.70	15.24	26	63.50	66.04
7	15.24	17.78	27	66.04	68.58
8	17.78	20.32	28	68.58	71.12
9	20.32	22.86	29	71.12	73.66
10	22.86	25.40	30	73.66	76.20
11	25.40	27.94	31	76.20	78.74
12	27.94	30.48	32	78.74	81.28
13	30.48	33.02	33	81.28	83.82
14	33.02	35.56	34	83.82	86.36
15	35.56	38.10	35	86.36	88.90
16	38.10	40.64	36	88.90	91.44
17	40.64	43.18	37	91.44	93.98
18	43.18	45.72	38	93.98	96.52
19	45.72	48.26	39	96.52	99.06
20	48.26	50.80	40	99.06	101.6
21	50.80	53.34			



喬訊電子工業股份有限公司  
CHYAO SHIUNN  
ELECTRONIC INDUSTRIAL LTD.

PART NO JS-11791SFTD-XX  
2.54mm SIP Socket(Single Row)

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	.0 ±0.30	△	XXX	XXX	XXXX/XX/XX	△			
CHECKED BY	PROJ	VER NO.	.00 ±0.20	△	ECR RoHS Compliant	XXX	2006/04/01	△			
黃科源		a4	.000 ±0.10	△	ECR 200812-010	黃科源	2008/12/10	△			
DRAWN BY	DATE	SIZE	ANGLE		電氣規格修定	吳弘文	2013/10/08		CUSTOMER		
吳弘文	2013/10/08	A4	0° ±1°	△					Conforms to The RoHS Instruction		
			.0° ±	△							
			SHEET 1/1	△							