



喬訊電子工業股份有限公司
CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



<http://www.chyaoshiunn.com.tw> E-mail: cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	
Subject: JS-2001M-TX JS-2001M-XX JS-1001M-XXGW Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.

This specification is referred to 2.50mm DIP series wire to board connector.

*本規格書內容係提供 2.50 mm DIP 系列產品相關參考，
其用途為電線端相接於電路板端連接器*

-INDEX-

- 1.0 **Product Name/Part Number & Drawing Number.** (產品名稱 / 產品型號及圖面型號)
- 2.0 **Construction/Dimensions/Material & Surface Finish.**(材質以及表面鍍層)
- 3.0 **Characteristic.**(產品特性)
- 4.0 **Specimen.**(樣本圖示)
- 5.0 **Applicable Standards.**(適用規範)
- 6.0 **Mechanical Performance.**(機械性能)
- 7.0 **Electrical Performance.**(電氣性能)
- 8.0 **Environmental Performance.**(環境性能)
- 9.0 **Insertion Force (I.F.) & Withdrawal Force (W.F.) for user reference** (插入力與拔出力參考規格)
- 10.0 **Remark** (備註).

REV. (版次)	Revision Record (改版變更原因)	Date(日期)	ECN No



喬訊電子工業股份有限公司
CHYAO SHIUNN ELECTRONIC INDUSTRIAL LTD.
 7FL., NO.17, LANE 3, SEC.1 CHUNG CHENG EAST RD.,
 TAMSHUI, TAIPEI, TAIWAN, R.O.C.
 TEL: 886-2-2629-9955 (REP) FAX: 886-2-2626-6677



<http://www.chyaoshiunn.com.tw> E-mail: cs@chyaoshiunn.com.tw

Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	
Subject: JS-2001M-TX JS-2001M-XX JS-1001M-XXGW Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.

1.0 Product Name/Part Number & Drawing Number(產品名稱 / 產品型號及圖面型號):

Product Name		Part Number(零件型號)	Drawing Number(圖面型號)
Crimp Terminal		JS-2001M-T	
Housing		JS-2001M-XX	
Wafer	Straight (直立式)	JS-1001M-XXGW	

Note: (xx) The number of the circuits 08,10,12

2.0 Construction/Dimensions/Material & Surface Finish(材質以及表面鍍層):

Part Name(零件名稱)		Material(材質)	Surface Finish(表面鍍層)
Crimp Terminal (柳壓端子)	JS-2001M-T	Phosphor Bronze	Tin-Plated
	JS-2001M-TB	Brass	
Housing (電線端連接器)		Nylon 66	UL 94V-0
Wafer (電路板端連接器)	Normal Square Pin (標準方型導體)	Brass	Sn120u" over Plated , Nickel 30u" under all over 表層鍍錫 120u",底層鍍鎳 30u"
	Square Pin		
	Base (膠座)	Nylon 66 Glow wire	UL 94V-0 Color : Nature

3.0 Characteristic(產品特性):

Item(項目)		Standard(標準規範)					
3.1	額定電流 Rated Current	Conductor	AWG	22#	24#	26#	28#
		Size	Area(mm ²)	0.342 mm ²	0.220 mm ²	0.14 mm ²	0.089 mm ²
		Amp AC/DC		3A	2A	1A	0.8A
3.2	額定電壓 Rated Voltage	250 V AC/DC					
3.3	Ambient Temperature Range 環境與操作溫度範圍	(操作使用溫度與濕度範圍) Operating Temp.: -40°C~+105°C ; 85% R.H. Max Including 30°C Terminal Temperature Rise at rated Current , (包括定額電流內 , 端子所產生 30°C 以下溫昇)					
3.4	Applicable Wire 適用電線	3.4.1	(金屬導體型號) Conductor Construction Size: AWG #22~#28				
		3.4.2	(電線絕緣材質外徑) Wire Insulation O.D.: 1.15mm~1.9mm				



Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	
Subject: JS-2001M-TX JS-2001M-XX JS-1001M-XXGW Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.

3.5	Storage of Package 包裝未拆封之保存	Temperature and Humidity Condition 溫濕度條件		Temperature 溫度 : -10°C~+40°C
		Term 保存期限	Housing Crimp Terminal & Wafer	Percentage Humidity 相對濕度 : 70 % Max
3.6	Floor Life 拆封後使用期限	Wafer	3 Months	
		Crimp Terminal		

4.0 Specimen(樣本圖示) :

Part Name / Part Number / Picture or Photograph 零件型號 / 零件名稱 / 樣本圖示			
Crimp Terminal JS-2001M-T/TB		Housing JS-2001M	
Wafer Straight JS-1001M			

5.0 Applicable Standards(適用規範):

ANSI/EIA 364 ; EIA/ECA 364 Testing method for electrical connectors.

電子連接器所適用之 ANSI/EIA 364 ; EIA/ECA 364 測試規範

6.0 Mechanical Performance(機械性能):

Item(項目)		Test Condition(測試條件)	Requirement(規格)
6.1	Insertion & Withdrawal Force 插入力與拔出力	Insert and withdrawal with connectors at the speed rate of 25.4±3mm/minute. (Excluding Plastic Detents 不包含膠座卡榫結合) 連接器兩端勘合，以每一分鐘 25.4±3 mm 的速率，作嵌入與拔出往返測試 (EIA/ECA 364-13D)	Refer to 9.1 Table1. 參照第 9.1 項 表格 1
6.2	Wire Pullout Force(Axial) 電線脫離端子包覆之 拔出力(軸向)	Pull out the cable from with contact terminal at the speed rate of 25.4±3 mm/minute. 對端子所包覆電線，施以每一分鐘 25.4±3 mm 速率之軸向拔出力 (EIA 364-08B)	AWG#22 size wire 4.0kgf/Min.(39.2N 牛頓)
			AWG#24 size wire 3.0kgf/Min.(29.4N 牛頓)
			AWG#26 size wire 2.0kgf/Min.(19.6N 牛頓)
			AWG#28 size wire 1.0kgf/Min.(9.8N 牛頓)



Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	
Subject: JS-2001M-TX JS-2001M-XX JS-1001M-XXGW Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.
Item(項目)	Test Condition(測試條件)		Requirement(規格)
6.3	Crimp Terminal Retention Force (in Housing) 柳線端子與膠座之間拔出力	Axial pullout force on the terminal in the housing at the speed rate of 25.4 ± 3 mm per minute. (EIA/ECA 364-29C) 對於已經存在於膠座當中柳線端子，施以每一分鐘 25.4 ± 3 mm 速率之軸向拔出力	單一接觸點 Per Contact 最小容許值 1.5kgf/Min.
6.4	Crimp Terminal Insertion Force (in Housing) 柳線端子與膠座之間插入力	Insert the crimped terminal into the housing at the speed rate of 25.4 ± 3 mm per minute.將端子插入膠座中，施以每一分鐘 25.4 ± 3 mm 速率之軸向插入力	單一接觸點 Per Contact 最大容許值 0.5kgf/Max.
6.5	Square Pin Retention Force (in Base) 方型導體與膠座之間拔出力	Axial pullout force on the square pin in the base at the speed rate of 25.4 ± 3 mm per minute. (EIA/ECA 364-29C) 對於已經存在於膠座當中方型導體，施以每一分鐘 25.4 ± 3mm 速率之軸向拔出力	單一接觸點 Per Contact 最小容許值 1.0kgf/Min.
6.6	Lock Strength 卡勾強度	Mated Connectors, apply axial pull out force at the speed rate of 25±3mm/min. 配對連接器，以 25±3mm / min 的速度施加軸向拉力。	8,10,12 CKT: 4.0 Kgf min.

7.0 Electrical Performance(電氣性能) :

Item(項目)	Test Condition(測試條件)		Requirement(規格)
7.1	(Low –Signal Level) Contact Resistance (低階信號) 接觸阻抗	A maximum voltage of 20mV and a maximum current of 100mA are applied to the mate connector. (EIA/ECA 364-23C) 對組合狀態下之連接器，於其兩端施以最大電壓 20mV 以及最大電流 100mA (Does not include wire resistance 不包含電線阻抗)	Contact Resistance: 20 milliohms Max. 最大容許值. 20m 歐姆
7.2	Insulation Resistance 絕緣阻抗	Apply 500V D/C for 1 minute between adjacent contacts to measure the insulation resistance. 對相鄰兩接觸導體，於一分鐘時間內施予 500V D/C 電壓，並量測其間絕緣阻抗值 (EIA 364-21C)	Insulation Resistance: Initial 1000 megohms Min 最初容許值. 1000M 歐姆
7.3	Withstanding Voltage 耐電壓	Apply 1000V A/C (rms) for 1 minute and the leakage current shall not exceed 0.5mA to the adjacent terminal and ground of the mate connectors. (EIA 364-20C) 對組合狀態下連接器，於其相鄰兩導體末端各施以電壓 1000V A/C(實效值) 時間 1 分鐘，且漏電流必須小於 0.5mA(毫安培)	No breakdown or flashover. 無損毀或者產生火花



Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	
Subject: JS-2001M-TX JS-2001M-XX JS-1001M-XXGW Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.

Item(項目)	Test Condition(測試條件)	Requirement(規格)
7.4 Contact Resistance on crimped portion 鉚接 端接觸阻抗	Crimp the applicable wire on to the terminal, measure by dry circuit 20mV maximum 10mA. (EIA/ECA 364-23C) 壓接端子上的適用電線，並通過乾電路 20mV 最大 10mA 進行測量。	Contact Resistance: 50 milliohms Max. 最大容許值. 20m 歐姆

8.0 Environmental Performance(環境性能) :

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.1 Durability 耐久性	Mate Connectors up 30 Cycles at a Maximum rate of 10 cycles Per minute prior to environmental test (EIA/ECA 364-09C) 以組合狀態下連接器且未經環境測試，依每分鐘內進行10次嵌入與拔出之最大速率，連續30次嵌入與拔出往返測試	(After the test) Contact resistance : 經耐久性試驗後接觸阻抗： 40 mΩ Max
8.2 Temperature Rise (Via Current Cycling) 溫昇 (經由電流循環操作)	Mate connector . measure the temperature rise of contact when the maximum rated current is passed 以組合狀態下連接器，通過最大容許電流量測其導體溫度上昇值 (EIA 364-70B Conditions 1 . Method 1)	Mate connectors Temperature Rise: +30°C/Max. 組合狀態下之連接器溫度上昇 最大容許值 +30°C
8.3 Vibration 耐振動	A mated connector shall be mounted on a printed Circuit board and subjected to a vibration test of the following conditions. During the test, test current continuity shall be checked. After the test, contact resistance shall be measured. 以組合狀態下連接器焊接於電路板作為試驗樣品,依照隨附如下規格要求,進行耐振動試驗，試驗過程中確認是否產生不連續電流(斷電)現象，並於試驗過後量測其接觸阻抗。 (EIA/ECA 364-28E-Condition 1) Frequency(頻率) : 10~55~10 Hz/minute. Amplitude (振幅) : 1.5 mm P-P Direction (方向) :1. Axis of up and down.上下軸向(Y 軸) 2. Axis of right the left. 左右軸向(X 軸) 3. Axis of front and back.前後軸向(Z 軸) Period(週期) : 2 hours for each direction. (每一個軸向持續 2 小時)	Initial Contact Resistance : 20 milliohms Max. 接觸阻抗最初容許值: 20m 歐姆 (After the test) Contact Resistance: 40 milliohms Max. 經耐振動試驗後接觸阻抗： 最大容許值 40m 歐姆 No discontinuity current is longer than 1 microsecond. 電流中斷現象， 時間不可多於1微秒



Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	2019/08/26
Subject: JS-2001M-TX JS-2001M-XX JS-1001M-XXGW Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.

Item(項目)		Test Condition(測試條件)	Requirement(規格)
8.4	Humidity (Steady State) 恆溫恆濕	<p>A mated connector shall be placed in a humidity chamber of the following conditions. After the test, the contact resistance, the insulation resistance and the dielectric withstanding voltage shall be measured.</p> <p>以組合狀態下連接器放置於恆定溫度與濕度的空間，依照隨附如下規格要求，進行恆溫恆濕試驗，並於試驗過後量測其接觸阻抗、絕緣阻抗、以及耐電壓測試。</p> <p>(EIA 364-31B Conditions III. Method A)</p> <p>Temperature(溫度) : 60±2°C.</p> <p>Relative Humidity(相對濕度) : 90%~95% (RH).</p> <p>Period(週期) : 96 hours continuously. (持續 96 小時)</p>	<p>(After the test)</p> <p>Contact Resistance:</p> <p>40 milliohms Max.</p> <p>經恆溫恆濕試驗後接觸阻抗： 最大容許值. 40m 歐姆</p>
			<p>(After the test)</p> <p>Insulation Resistance :</p> <p>100 Megohms Min.</p> <p>經恆溫恆濕試驗後絕緣阻抗： 最小容許值. 100M 歐姆</p>
			<p>經恆溫恆濕試驗後耐電壓：</p> <p>(After the test)</p> <p>Withstanding Voltage:</p> <p>1000V A/C for 1 minute</p>
8.5	Thermal Shock 冷熱衝擊	<p>A mated connector shall be subjected to a thermal shock test of the following conditions. After the test, the contact resistance, the insulation resistance and the dielectric withstanding voltage shall be measured.</p> <p>以組合狀態下連接器作為試驗樣品，依照隨附如下規格要求，進行冷熱衝擊試驗，並於試驗過後量測其接觸阻抗、絕緣阻抗、以及耐電壓測試。</p> <p>(EIA/ECA 364-32D Conditions I. Method A)</p> <p>One Cycle Consists Of:</p> <p>-55 +0/-3°C for 30 minutes. → Room Temp.5 minutes</p> <p>105+3/-0°C for 30 minutes. → Room Temp.5 minutes</p> <p>Total Cycles: 5 Cycles.</p> <p>以-55+0/-3°C 溫度持續 30 分鐘，經室溫 5 分鐘，而後再以 85+3/-0°C 溫度持續 30 分鐘，再經室溫 5 分鐘，構成一次冷熱循環，總計循環次數 5 次。</p>	<p>Same as paragraph 8.4</p> <p>同 8.4 章節</p>



Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	
Subject: JS-2001M-TX JS-2001M-XX JS-1001M-XXGW Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.

Item(項目)		Test Condition(測試條件)	Requirement(規格)
8.6	Thermal Aging 高溫老化試驗	<p>A mated connector shall be placed in a heat oven of the following conditions. After the test, contact resistance shall be measured. (EIA 364-17B Conditions III . Method A)</p> <p>以組合狀態下連接器放置於加熱烤箱當中，依照隨附如下規格要求，進行高溫老化試驗，並於試驗過後量測其接觸阻抗。</p> <p>Temperature(溫度): 105±2℃.</p> <p>Period(週期): 96 hours continuously . (持續 96 小時)</p>	<p>Initial Contact Resistance : 20 milliohms Max.</p> <p>接觸阻抗最初容許值:20m 歐姆</p> <p>(After the test)Contact Resistance :40 milliohms Max. .</p> <p>經高溫老化試驗後接觸阻抗 :</p>
8.7	Salt Spray 鹽水噴霧	<p>A mated connector shall be subjected to a Salt Spray test of the following conditions. After the test , the specimen shall be washed with running water and dried naturally before the measurement of contact resistance.以組合狀態下連接器作為試驗樣品，依照隨附如下規格要求，進行鹽水噴霧試驗，試驗過後將樣品用清水沖洗並經過自然風乾，而後量測其接觸阻抗。(EIA 364-26B Conditions B)</p> <p>Density(鹽水密度): 5 % in weight. Temperature(溫度): 35±2℃.</p> <p>Period(週期) : Terminal or Contact (Stamping after tin plated for 8 hours) ; Terminal or contact (Stamping before tin plated for 48 hours) 端子或導體 (先電鍍後沖壓 8 小時) ; 端子或導體 (先沖壓後電鍍 48 小時)</p> <p>Salt spray test only define the plating area,without plating area (as copper cross section) will not be defined. 鹽水噴霧測試只判定電鍍區域,無電鍍區域(如折斷面裸銅)則不做判定</p>	<p>Initial Contact Resistance : 20 milliohms Max.</p> <p>接觸阻抗最初容許值:20m 歐姆</p> <p>(After the test) Contact Resistance: 40 milliohms Max.</p> <p>經鹽水噴霧試驗後接觸阻抗 : 最大容許值. 40m 歐姆</p>
8.8	Cold (Low Temperature) 耐寒試驗	<p>A mated connector shall be placed in a cold chamber of the following conditions.After the test,leave the specimen at room temperature for 1~2 hours before the contact resistance shall be measured. 以組合狀態下連接器放置於低溫空間內，依照隨附如下規格要求，進行耐寒測試，經試驗過後將樣品放置室溫於 1~2 小時,再量測其接觸阻抗。(EIA-364-59A Condition D;Condition 4)</p> <p>Temperature(溫度): -40 ± 3℃</p> <p>Period(週期) : 96 hours continuously. (持續 96 小時)</p>	<p>Initial Contact Resistance : 20 milliohms Max.</p> <p>接觸阻抗最初容許值:20m 歐姆</p> <p>(After the test) Contact Resistance: 40 milliohms Max.</p> <p>經耐寒試驗後接觸阻抗 : 最大容許值. 40m 歐姆</p>




Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	
Subject: JS-2001M-TX JS-2001M-XX JS-1001M-XXGW Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.

Item(項目)	Test Condition(測試條件)	Requirement(規格)
8.9 Solder Ability 焊錫性	Fluxed soldering section of header shall be dipped in solder of the following conditions. (EIA 364-52B) 將連接器 pin 針基板嵌入端，接觸熱溶狀錫料，依照隨附如下規格要求，進行焊錫性試驗 Solder Temperature (焊錫溫度) : 245 ± 5°C . Immersion Period (沉浸週期) : 3±0.5 Seconds (操作方式)：零件焊錫位置，距離導體末端 1.5mm Method : 1.5mm from square pin tip	Solder entirely 95% of immersed area must show no voids or pin holes. 焊料覆蓋面積必須達到 95% 而且不能產生氣孔或空隙
8.10 Resistance To Soldering Heat 焊錫耐熱性	By Wave Soldering：使用波峰焊適用溫度範圍 Refer to Temperature Profile 請參考 8.10.1.1 溫度曲線圖 By reflow soldering 回流焊適用溫度範圍： Refer to Temperature Profile 請參考 8.10.1.2 溫度曲線圖 By soldering iron 手工烙鐵焊錫適用溫度範圍： 350 ± 5°C 3±0.5 Seconds . (EIA/ECA 364-56C Procedure 3. Conditions A) (操作方式)：零件焊錫位置，距離導體末端 1.5mm Method : 1.5mm from square pin tip	No deformation or damage. 不可有變形或損壞

Notes : Flowing Mixed Gas (EIA 364-65A) shall be conduct by Customer request 混合流動氣體測試依照客戶需求

8.10.1 Temperature Profile(溫度曲線圖)：


8.10.1.1 Wave Peak Soldering In- General Process 波峰焊一般制程





Type Document	Product Specification	Revised /Edition	A
Date Issued	2021/03/29	Data Revised	2019/08/26
Subject: JS-2001 JS-2001-T/B JS-1001-02~06(XXXX)XX JS-1001R-02~06(XXXX)XX Pitch 2.50mm Series Wire to Board Connector			Issued By: Engineering Dept.

8.10.1.2 Reflow Soldering In-Lead Free Process 回流焊無鉛制程:



9.0 Tables & Attachments

9.1 Table 1. Insertion Force (I.F.) & Withdrawal Force (W.F.) for user reference:

Unit : Kg/f

No. Of Circuits 極數	AT INITIAL 首次嵌入與拔出(初始值)		AT 30 TH 30次嵌入與拔出之後
	I.F. (MAX) 嵌入力	W.F. (MIN) 拔出力	W.F. (MIN) 拔出力
	08	7.8	1.15
10	9.0	1.45	1.3
12	10.2	1.85	1.6

10.0 Remark(備註) : Any change or revision for the product specification will not be announced in advance.

Please contact our sales representative for the latest information.

有關規格書內容經變更或改版，如未能夠及時發佈與通知，煩請連絡我司業務人員以提供產品最新資訊

Reviewed: Tom Shih Approved: Erin Chou Verified: Eddie Chiang